ALFA625E1HDS



Family	Professional ovens
Subfamily	Convection oven 6 trays en 600x400 mm or GN1/1
Oven type	Convection oven with humidification
Oven control	Electronic
Trays capacity	6 trays EN 600x400 mm or GN1/1 (excluding flat trays and grids)
Power supply	400 V 3N~ / 16 A / 10,5 kW / 50-60 Hz
Steam generation	Direct
Program storage with application	Not available
Maximum depth with open door	1521 mm
Adjustable feet	Yes
Net weight	77,000 kg
Product dimensions WxDxH	798x757x793 mm
EAN code	8017709322946

Target

Solutions	Coffee shops/Wine bars; Hotels; Restaurants/Pubs; Bakery/Pastry making; Frozen bakery industry; Food retail	**Suggested for**	Bakery

Aesthetics

Colour	Stainless steel	**Digit display color**	White
Door with stainless steel stripes	Yes	**Front panel**	Yes
Display type	Digital TFT	**Logo**	Smeg printed

Controls

Storable programs number	100	**Chimney regulation**	Yes
Timer setting range	1-60 minutes + endless	**HACCP data**	Yes
Cooking steps	3 + pre-heating		

Programme / Functions

Backing functions

 Convection

 Convection with humidification

 Core probe

 Core probe + Δ t

Adjustable fan speed


 Double speed fan

Options

Combinable hood	K4610X

Construction

Oven materials	Stainless steel / glass / plastics
Cavity dimensions (wxdxh)	672x437x546 mm
Gross volume	184,8 lt
Net volume	165,6 lt
Internal net volume	127,3 lt
Cavity material	Stainless steel
Shelves number	6
Tray frame support	Chromed wire
Shelves distance	77 mm
Door construction	Double glass
Door opening	Lateral - left hinge
Handle type	Rotating
Glass	Openable with hinge
Fan type and number	2 contrarotating with timed direction reversal
Fan motor power	200W
Engine rpm	Dual speed
Motor rpm in standard speed	2850 rpm
Motor rpm in low speed	1450 rpm
Water injection on each fan	Yes
Humidification levels	5 + manual
Exhaust position	Back
Components cooling system	Yes
Timer type	Electrical
Temperature range	50-280°C
End cooking signal	Yes
Safety switch with open door	Yes
Manual reset safety thermostat	Yes
Predisposition for core probe	Yes
Removable deflector	Yes
Lighting	2 LED lamps
Light power	40 W
USB port	Yes
Water load pipe	Yes
Power cable length	170 cm
Back panel	Galvanized
IPX protection	IPX3



Q	MORSETTO EQUIPOTENZIALE EARTH TERMINAL
E	CAVO ALIMENTAZIONE ELETTRICA ELECTRICITY SUPPLY CABLE
C	TUBO DI CARICO FILLER HOSE
S	TUBO DI SCARICO *(solo su alcuni modelli)* DRAIN HOSE *(on some models only)*
D	TUBO DI CARICO PER DOCCETTA LAVAGGIO *(solo su alcuni modelli)* WATER SUPPLY MANUAL WASHING SYSTEM *(on some models only)*

Not included accessories




3805

Flat chrome-plated wire grid (4pcs)



3927

Air flow reducer kit for ovens ALFA410, 420, 625, 1035




TF11XH2

Perforated aluminium GN1/1 tray, 20 mm height



3743

Flat aluminium tray (4pcs)



TMF11TH2

GN 1/1 non-sticking microperforated tray, 20 mm height

SVRPP625

Connector kit for two stacked ALFA625 or ALFA625+ALFA420/425 models and hood



T11XH20

2cm height aluminium GN1/1 tray, 20 mm height



SVRPP420-625

Connector kit for two stacked ALFA420+420 or ALFA420+625 models and hood




T11XH65

GN1/1 aluminium tray, 65 mm height



T11TH20

GN1/1 non-stick tray, 20 mm height



G11X8P

8 vertical GN1/1 chicken grid


KITSC

Core temperature probe for EHDS models



RGN11-625-2

Support kit for grids or flat trays GN1/1 suitable for ALFA625 models




G11T

Non-stick GN1/1 tray




3751

Flat perforated aluminium tray (4pcs)



3810

Waved grid for baguettes (4pcs)



T8S11T

8 holes GN 1/1 non-sticking tray



T11TH40

GN1/1 non-stick tray, 40 mm height

Symbols glossary (TT)



Core probe



Core probe baking by temperature difference (Δ t)



Fan forced heating



Fan forced heating with humidity injection



Double speed fan