BOLT 64

COMPAK

Workflow Engineering

Designed to satisfy the demands of coffee professionals, the **Bolt** offers two functional modes: **Predose** and **Fresh**.
Instant access to the grinding chamber for cleaning or burr replacement without losing the adjustment, thanks to the **Lock Load System**.
Burrs durability: **1.350 Kg***. **Long-lasting tempered steel K110** recommended for food use

Motor **630 W**
Burrs **Ø 64 mm**



KEY SPECIFICATIONS 230 V/50 Hz

Motor output	**630**	W
Revolutions per minute	**1.310**	rpm
Ø Burrs	**64**	mm
Espresso point production*	**2,8**	g/s
Hopper capacity	**1.250**	g
Height x width x depth	**660 x 231 x 384**	mm
Net weight	**16,69**	kg

* Production and durability based on a medium roast coffee and grinding point for Espresso. There is a direct relation between the wear of the burrs and the increase in time per dose

HIGHLIGHTED ELEMENTS

Predose Mode
Selection of 1 or 2 coffees previously ground

Fresh Mode
Selection of 1, 2 or 3 ground doses on demand

KEY FEATURES

- Micrometric **Parallel System** adjustment
- **Instant access** to the grinding chamber (LLS optional)
- **Coffee outlet enlightened** with leds
- **Motor with fan**
- **Adjustable** coffee outlet and fork

ELECTRONIC FEATURES

- **2.8" TFT touchscreen**
- **Multilanguage** display
- **Portafilter detector**
- **Menu access** protection **with password**
- Dose counter, both **absolute and relative**
- **Wear and changing burrs** alarm
- **Screensaver**