# E10 OD

COMPAK

Innovation intersects tradition

**Instant access** to the grinding chamber for cleaning or burr replacement without losing the adjustment, thanks to the **Lock Load System**.
Micrometric **Parallel System** adjustment.
**Long-lasting Red Speed burrs**. **Durability: 8.000 Kg*.**

Motor **950 W**
Burrs **Conical Ø 68 mm**




## KEY SPECIFICATIONS 230 V/50 Hz

| | | |
|---|---|---|
| Motor output | **950** | W |
| Revolutions per minute | **340** | rpm |
| Ø Burrs | **Conical 68** | mm |
| Espresso point production* | **4,3** | g/s |
| Hopper capacity | **1.250** | g |
| Height x width x depth | **660 x 230 x 385** | mm |
| Net weight | **19,5** | kg |

* Production and durability based on a medium roast coffee and grinding point for Espresso. There is a direct relation between the wear of the burrs and the increase in time per dose

## KEY FEATURES

- Micrometric **Parallel System** adjustment
- **Instant access** to the grinding chamber (LLS standard)
- **Coffee outlet illuminated** with LEDs
- **Motor with fan**
- **Adjustable fork** in height and depth
- Front-mounted **refill button**

## ELECTRONIC FEATURES

- **2.8" TFT touchscreen**
- **Multilanguage** display
- **Portafilter detector** (optional)
- **Menu access** protection **with password**
- Dose counter, both **absolute and relative**
- **Wear and changing burrs** alarm
- **Screensaver**