E6 OD

COMPAK

Innovation intersects tradition

Direct access to the grinding chamber for cleaning or burr replacement without losing the adjustment. **Lock Load System** optional.
Micrometric **Parallel System** adjustment.
Burrs made from long-lasting hardened steel K110. **Durability: 1.350 kg***. Optional **Red Speed burrs** durability: **2.500 kg***.

Motor **630 W**
Burrs **Ø 64 mm**



KEY SPECIFICATIONS 230 V/50 Hz

Motor output	**630**	W
Revolutions per minute	**1.290**	rpm
Ø Burrs	**64**	mm
Espresso point production*	**2,8**	g/s
Hopper capacity	**1.250**	g
Height x width x depth	**600 x 230 x 385**	mm
Net weight	**13,20**	kg

* Production and durability based on a medium roast coffee and grinding point for Espresso. There is a direct relation between the wear of the burrs and the increase in time per dose

KEY FEATURES

- Micrometric **Parallel System** adjustment
- **Direct access** to the grinding chamber (LLS optional)
- **Coffee outlet illuminated** with LEDs
- **Motor with fan**
- **Adjustable fork** in height and depth
- Front-mounted **refill button**

ELECTRONIC FEATURES

- **2.8" TFT touchscreen**
- **Multilanguage** display
- **Portafilter detector** (optional)
- **Menu access** protection **with password**
- Dose counter, both **absolute and relative**
- **Wear and changing burrs** alarm
- **Screensaver**