Data sheet

# ECIW62T

| SERIES | PRODUCT FAMILY | VERSION | MODEL |
|---|---|---|---|
| **650** | **INDUCTION PLATE** | **ELECTRIC** | **ECIW62T** |

## DESCRIPTION

INDUCTION COOKING TOP 1 ZONE WOK



## TECHNICAL DATA:

| | |
|---|---|
| STRUCTURE | TOP |
| WIDTH | 400 mm |
| DEPHT | 650 mm |
| HEIGHT | 295 mm |
| NET WEIGHT | 16 kg |
| VOLUME | 0.24 m3 |
| ELECTRIC POWER | 5 kW |
| PHASE | 3N |
| FREQUENCY | 50/60 Hz |
| VOLTAGE | 400 V |

SILKO ALI Group Srl

Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 10123720962

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 50.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2507533- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it

| SERIES | PRODUCT FAMILY | VERSION | MODEL |
|---|---|---|---|
| **650** | **INDUCTION PLATE** | **ELECTRIC** | **ECIW62T** |

## FEATURES:


Ceramic Cook Top for WOK, hermetically sealed to the top plate, the pot detection system activates heating as soon as a cooking pot is placed upon the cook top. Appliance made of stainless steel. Equipped with 1 cooking zone of 5 kW output. Selector switch with 6 power setting levels. Indicator lights signal heating activation and that the appliance is operating correctly.

## STANDARD ACCESSORIES:

## OPTIONAL ACCESSORIES:

| SERIES | PRODUCT FAMILY | VERSION | MODEL |
|---|---|---|---|
| 650 | INDUCTION PLATE | ELECTRIC | ECIW62T |

## INSTALLATION SCHEME




| | | | |
|---|---|---|---|
| E1 | SOCKET | 400 V | 3N |
| AF | COLD WATER | | |
| AC | HOT WATER | | |
| G | GAS | | |
| S | DRAINING | | |

NOTES FOR THE INSTALLER:
All water and gas connections must be fitted with a shut-off valve or ball valve.
Main gas connections must be provided of closing gate device.
Gas connections must not use welded tubes.
Gas connections must be jacketed according to current rules in the country.
Electric connections must be provided of safety switch and a minimum exit wire of 1,5 meter lenght ( except where otherwise required in the drawing).
All sockets must be built according to safety-rules in force. Suited for humid room and settled with necessary plug.
All electric connections must be provided of main switch.
The specification shown in this document are to be considered not bounding.
The company reserves the right to make technical changes at any moment.

SILKO ALI Group Srl
Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 10123720962

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 50.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2507533- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it