Data sheet

ECV64EVP

SERIES	PRODUCT FAMILY	VERSION	MODEL
650	**CERAMIC PLATE**	**ELECTRIC**	**ECV64EVP**



DESCRIPTION

EL. RANGE CERAMIC TOP 4 ZONES HIGH POWER
ON EL. CONVECTION OVEN

TECHNICAL DATA:

STRUCTURE	ON FAN ELECTRIC OVEN
WIDTH	700 mm
DEPHT	650 mm
HEIGHT	850 mm
NET WEIGHT	80 kg
VOLUME	0.73 m3
ELECTRIC POWER	14.2 kW
PHASE	3N
FREQUENCY	50/60 Hz
VOLTAGE	400 V

OVEN POWER	4.2 kW

SILKO ALI Group Srl

Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it

SERIES	PRODUCT FAMILY	VERSION	MODEL
650	**CERAMIC PLATE**	**ELECTRIC**	**ECV64EVP**

FEATURES:


Monoblock cooking range Series SNACK, high performance, ceramic cook top with 4 independent cooking zones. The cooking zones are framed by silkscreened circles on the ceramic surface and equipped with a signal light for residual heat. Four independent cooking zones: 4 x 2,5 kw Ø22cm. Electric convection oven (57x49x29.5h). Heating by means of by independently controlled top and bottom heating elements. Thermostat to adjust the temperature within a setting range from 50°C to 300°C. Cooking chamber made of stainless steel. Oven bottom AISI 430 th. 30/10. 4-position selector switch, safety thermostat. Signal light to check whether the appliance is operating correctly. Power rating 4.2 kW. Appliance equipped with height-adjustable stainless steel feet.

OPTIONAL ACCESSORIES:

• STAINLESS STEEL OVEN GRID	C70XGRFVS
• STAINLESS STEEL TRAY	C70XTFVS

SERIES	PRODUCT FAMILY	VERSION	MODEL
650	**CERAMIC PLATE**	**ELECTRIC**	**ECV64EVP**

INSTALLATION SCHEME



E1	SOCKET	400 V	3N
AF	COLD WATER		
AC	HOT WATER		
G	GAS		
S	DRAINING		

NOTES FOR THE INSTALLER:
All water and gas connections must be fitted with a shut-off valve or ball valve.
Main gas connections must be provided of closing gate device.
Gas connections must not use welded tubes.
Gas connections must be jacketed according to current rules in the country.
Electric connections must be provided of safety switch and a minimum exit wire of 1,5 meter lenght (except where otherwise required in the drawing).
All sockets must be built according to safety-rules in force. Suited for humid room and settled with necessary plug.
All electric connections must be provided of main switch.
The specification shown in this document are to be considered not bounding.
The company reserves the right to make technical changes at any moment.

SILKO ALI Group Srl
Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it