Data sheet

NEBG74GMC

SERIES	PRODUCT FAMILY	VERSION	MODEL
700	**GRIDDLES**	**GAS**	**NEBG74GMC**

DESCRIPTION

GAS FRYTOP 80 CM COMBINED CHROMED ON OPEN MODULE



TECHNICAL DATA:

STRUCTURE	OPEN BASE
WIDTH	800 mm
DEPHT	730 mm
HEIGHT	900 mm
NET WEIGHT	94 kg
VOLUME	0.5 m3
GAS POWER	14 kW

PLATE SIZE	735x530 mm
NR. COOKING ZONES	2

SILKO ALI Group Srl

Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it

SERIES	PRODUCT FAMILY	VERSION	MODEL
700	**GRIDDLES**	**GAS**	**NEBG74GMC**

FEATURES:


Gas Fry-Top, two independent cooking zones with 2/3 smooth 1/3 ribbed, tilted, chromed hotplate, Monoblock unit on open base. Cook top made of stainless steel AISI 304, thickness 15/10, pre-fitted for head-to head connection. Hotplate lowered 4 cm compared to worktop, sealed and welded for easy cleaning. Satin finish cooking surface, 6.5 cm cooling zone in the front part of the hotplate. Round grease drain hole, diam. 4 cm. Fat tray with a capacity of 2.5 lt. Heating by means of steel burner with stabilized flame, flames in 2 branches 4 rows for each zone, incl. pilotflame and safety thermocouple. Gas supply controlled via thermostatic safety valve with thermocouple. Cooking temperature is set manually within a temperature range from 110 to 280 °C. Automatic ignition via piezoelectric device with waterproof cap. Cooking surface 73.5x53 cm. Height-adjustable feet in stainless steel. Scraper for cooking plate included.


OPTIONAL ACCESSORIES:

• SCRAPER FOR FRY TOP	RBLR
• PLATE CLEANING CAP	KFTT
• SPLASHBACK 800	KFTP81

SERIES	PRODUCT FAMILY	VERSION	MODEL
700	**GRIDDLES**	**GAS**	**NEBG74GMC**

INSTALLATION SCHEME





E1	SOCKET		
AF	COLD WATER		
AC	HOT WATER		
G	GAS	Ø 1/2"	100 mm
S	DRAINING		

NOTES FOR THE INSTALLER:
All water and gas connections must be fitted with a shut-off valve or ball valve.
Main gas connections must be provided of closing gate device.
Gas connections must not use welded tubes.
Gas connections must be jacketed according to current rules in the country.
Electric connections must be provided of safety switch and a minimum exit wire of 1,5 meter lenght (except where otherwise required in the drawing).
All sockets must be built according to safety-rules in force. Suited for humid room and settled with necessary plug.
All electric connections must be provided of main switch.
The specification shown in this document are to be considered not bounding.
The company reserves the right to make technical changes at any moment.

SILKO ALI Group Srl
Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it