Data sheet

NEBG92TRC

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**GRIDDLES**	**GAS**	**NEBG92TRC**

DESCRIPTION

GAS FRY TOP 40 CM RIBBED CHROMED TOP



TECHNICAL DATA:

STRUCTURE	TOP
WIDTH	400 mm
DEPHT	900 mm
HEIGHT	330 mm
NET WEIGHT	60 kg
VOLUME	0.2 m3
GAS POWER	10.5 kW

PLATE SIZE	335X700 mm
NR. COOKING ZONES	1

SILKO ALI Group Srl

Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**GRIDDLES**	**GAS**	**NEBG92TRC**

FEATURES:


Gas Fry-Top, top version, one cooking zone with ribbed, chromed, tilted cooking plate. Cook top made of stainless steel AISI 304, thickness 20/10, pre-fitted for head-to head connection. Top thickness 20/10. Hotplate lowered 4 cm compared to worktop, sealed and welded for easy cleaning. Cooking surface coated with polished hard chrome and 6.5 cm cooling area in the front of the hotplate. Round grease drain hole, diam. 4cm. Fat tray with a capacity of 1.5 lt. Heating by means of steel burner with stabilized flame, flames in 2 branches 4 rows, incl. pilotflame and safety thermocouple. Gas supply controlled via thermostatic safety valve with thermocouple. Thermostatic temperature setting ranging from 100 to 280°C. Safety thermostat switches on if the operating thermostat is not working. Automatic piezoelectric ignition with waterproof cap. Cooking surface 34.5x70cm. Height-adjustable feet. Scraper for cooking plate included.

OPTIONAL ACCESSORIES:

• SCRAPER FOR FRY TOP	RBLR
• PLATE CLEANING CAP	KFTT
• SPLASHBACK 400	KFTP41

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**GRIDDLES**	**GAS**	**NEBG92TRC**

INSTALLATION SCHEME



E1	SOCKET		
AF	COLD WATER		
AC	HOT WATER		
G	GAS	Ø 1/2"	600 mm
S	DRAINING	Ø 40 mm	

NOTES FOR THE INSTALLER:
All water and gas connections must be fitted with a shut-off valve or ball valve.
Main gas connections must be provided of closing gate device.
Gas connections must not use welded tubes.
Gas connections must be jacketed according to current rules in the country.
Electric connections must be provided of safety switch and a minimum exit wire of 1,5 meter lenght (except where otherwise required in the drawing).
All sockets must be built according to safety-rules in force. Suited for humid room and settled with necessary plug.
All electric connections must be provided of main switch.
The specification shown in this document are to be considered not bounding.
The company reserves the right to make technical changes at any moment.

SILKO ALI Group Srl
Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it