Data sheet

NECG96G

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**GAS RANGES**	**GAS**	**NECG96G**

DESCRIPTION

GAS RANGE 6 BURNERS ON OPEN MODULE



TECHNICAL DATA:

STRUCTURE	OPEN BASE
WIDTH	1200 mm
DEPHT	900 mm
HEIGHT	900 mm
NET WEIGHT	124 kg
VOLUME	1.5 m3
GAS POWER	42 kW

NR. COOKING ZONES	6

SILKO ALI Group Srl

Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**GAS RANGES**	**GAS**	**NECG96G**

FEATURES:


Gas Range 6 burners, Monoblock unit on open base. Pressed stainless steel cook top (AISI 304), thickness 20/10, pre-fitted for head-to-head connection and installation of the water column (accessory). Standard device with 6 main burners, max. output 4 x 6 kW and 2 x 9 kW, hermetically sealed to top. Constant power adjustment within a range of 2.5 to 9 kW via safety tap with thermocouple. Ignition of the main burner via a steady low-consumption pilot burner (170 W). The pilot burner and thermocouple are placed underneath the main burner body to provide protection against accidental impacts and spills. Top with radiused corners for easy cleaning, equipped with RAAF enamelled cast iron grids (acid, alkali and flame resistant). Height-adjustable feet in stainless steel.

OPTIONAL ACCESSORIES:

• ELECTRIC IGNITION KIT	EXACEL6
• KIT WATER LOAD / DRAIN ON BURNER SUPPORT BASIN	EXSCA6
• CAST IRON GRID FOR ONE BURNER	EGG9
• STAINLESS STEEL GRID FOR ONE BURNER	EGT9
• CAST IRON SMOOTH HOTPLATE	EGHL
• CAST IRON RIBBED HOTPLATE	EGHR

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**GAS RANGES**	**GAS**	**NECG96G**

INSTALLATION SCHEME



E1	SOCKET		
AF	COLD WATER	Ø 1/2"	100 mm
AC	HOT WATER		
G	GAS	Ø 1/2"	100 mm
S	DRAINING	Ø 40mm N°2	0 mm

NOTES FOR THE INSTALLER:
All water and gas connections must be fitted with a shut-off valve or ball valve.
Main gas connections must be provided of closing gate device.
Gas connections must not use welded tubes.
Gas connections must be jacketed according to current rules in the country.
Electric connections must be provided of safety switch and a minimum exit wire of 1,5 meter lenght (except where otherwise required in the drawing).
All sockets must be built according to safety-rules in force. Suited for humid room and settled with necessary plug.
All electric connections must be provided of main switch.
The specification shown in this document are to be considered not bounding.
The company reserves the right to make technical changes at any moment.

SILKO ALI Group Srl
Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it