Data sheet

NECI92T

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**INDUCTION PLATE**	**ELECTRIC**	**NECI92T**

DESCRIPTION

ELECTRIC RANGE INDUCTION TOP 2 ZONES TOP VERSION



TECHNICAL DATA:

STRUCTURE	TOP
WIDTH	400 mm
DEPHT	900 mm
HEIGHT	320 mm
NET WEIGHT	50 kg
VOLUME	0.22 m3
ELECTRIC POWER	10 kW
PHASE	3
FREQUENCY	50/60 Hz
VOLTAGE	400 V

PLATE SIZE	350x700 mm
NR. COOKING ZONES	2

SILKO ALI Group Srl

Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**INDUCTION PLATE**	**ELECTRIC**	**NECI92T**


FEATURES:

Induction cook top Top version Top plate in stainless steel AISI 304, thickness 20/10, pre-fitted for head-to-head connection, ceramic top thickness 6 mm sealed to the top plate, the pot detection system activates heating as soon as a cooking pot is placed upon the cook top. Equipped with 2 independent cooking zones of 5 kW output. Cooking zones are framed by silkscreened circles on the ceramic surface. Selector switch with 10 power settings. Indicator lights signal heating activation and that the appliance is operating correctly. Incorporated Power-Box, main safety sensor. Height-adjustable feet.

OPTIONAL ACCESSORIES:

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**INDUCTION PLATE**	**ELECTRIC**	**NECI92T**

INSTALLATION SCHEME



E1	SOCKET	400 V	3
AF	COLD WATER		
AC	HOT WATER		
G	GAS		
S	DRAINING		

NOTES FOR THE INSTALLER:
All water and gas connections must be fitted with a shut-off valve or ball valve.
Main gas connections must be provided of closing gate device.
Gas connections must not use welded tubes.
Gas connections must be jacketed according to current rules in the country.
Electric connections must be provided of safety switch and a minimum exit wire of 1,5 meter lenght (except where otherwise required in the drawing).
All sockets must be built according to safety-rules in force. Suited for humid room and settled with necessary plug.
All electric connections must be provided of main switch.
The specification shown in this document are to be considered not bounding.
The company reserves the right to make technical changes at any moment.

SILKO ALI Group Srl
Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it