Data sheet

NECIT92TE

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**INDUCTION PLATE**	**ELECTRONIC**	**NECIT92TE**

DESCRIPTION

ELECTRONIC INDUCTION RANGE FULL COVERAGE
2 ZONES TOP VERSION



TECHNICAL DATA:

STRUCTURE	TOP
WIDTH	400 mm
DEPHT	900 mm
HEIGHT	320 mm
VOLUME	0.22 m3
ELECTRIC POWER	14 kW
PHASE	3
FREQUENCY	50/60 Hz
VOLTAGE	400 V

PLATE SIZE	350x700 mm
NR. COOKING ZONES	2

SILKO ALI Group Srl

Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**INDUCTION PLATE**	**ELECTRONIC**	**NECIT92TE**

FEATURES:

Electronic Induction Range Full Coverage. Top plate in stainless steel AISI 304, thickness 20/10, pre-fitted for head-to-head connection, ceramic top thickness 6 mm sealed to the top plate, the pot detection system activates heating as soon as a cooking pot is placed upon the cook top. Equipped with 2 independent cooking zones of 7 kW output. Cooking zones are framed by silkscreened circles on the ceramic surface. Control and operational settings via backlit computer with touch technology, black musk. Temperature setting with 10 power levels, three timers integrated with buzzer and auto shut off to decrease power consumption, standby function with adjustable set point, audible and visual signals for set timings and temperatures, temperature also displayed when appliance is turned off, auto diagnose system to check that appliance is operating correctly and low voltage digital inputs to optimize power consumption. Incorporated Power-Box, main safety sensor. Height-adjustable feet in stainless steel.

OPTIONAL ACCESSORIES: