Data sheet

NECV92T

SERIES	PRODUCT FAMILY	MODEL
900	**CERAMIC PLATE**	**NECV92T**

DESCRIPTION

ELECTRIC RANGE CERAMIC TOP 2 ZONES TOP VERSION



TECHNICAL DATA:

STRUCTURE	TOP
WIDTH	400 mm
DEPHT	900 mm
HEIGHT	320 mm
VOLUME	0.2 m3
ELECTRIC POWER	8 kW
PHASE	3N
FREQUENCY	50/60 Hz
VOLTAGE	400 V

PLATE SIZE	350x700 mm
NR. COOKING ZONES	2

SILKO ALI Group Srl

Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it

SERIES	PRODUCT FAMILY	MODEL
900	**CERAMIC PLATE**	**NECV92T**


FEATURES:

Ceramic Cook top made of stainless steel AISI 304. Top thickness 20/10, pre-fitted for head-to-head connection. Equipped with 2 independent cooking zones, each one with square radiant hotplates, dim. 280x280 mm with 4 kW output and controlled via power regulator. Ceramic top, thickness 6 mm, sealed to the top plate. Max. temperature 400°C in 3 minutes. Dimensions of the hotplate in cm 35x70. The cooking zones are framed by silkscreened circles on the ceramic surface and equipped with a signal light for residual heat. Signal light checks whether the appliance is operating correctly. Height-adjustable feet.

OPTIONAL ACCESSORIES:

SERIES	PRODUCT FAMILY	MODEL
900	**CERAMIC PLATE**	**NECV92T**

INSTALLATION SCHEME



E1	SOCKET	400 V	3N
AF	COLD WATER		
AC	HOT WATER		
G	GAS		
S	DRAINING		

NOTES FOR THE INSTALLER:
All water and gas connections must be fitted with a shut-off valve or ball valve.
Main gas connections must be provided of closing gate device.
Gas connections must not use welded tubes.
Gas connections must be jacketed according to current rules in the country.
Electric connections must be provided of safety switch and a minimum exit wire of 1,5 meter lenght (except where otherwise required in the drawing).
All sockets must be built according to safety-rules in force. Suited for humid room and settled with necessary plug.
All electric connections must be provided of main switch.
The specification shown in this document are to be considered not bounding.
The company reserves the right to make technical changes at any moment.

SILKO ALI Group Srl
Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it