Data sheet

# NEFE92122E

| SERIES | PRODUCT FAMILY | VERSION | MODEL |
|---|---|---|---|
| **900** | **FRYER** | **ELECTRONIC** | **NEFE92122E** |

## DESCRIPTION

ELECTRONIC FRYER 1 WELL 22 LT.



## TECHNICAL DATA:

| | |
|---|---|
| STRUCTURE | FLOOR |
| WIDTH | 400 mm |
| DEPHT | 900 mm |
| HEIGHT | 900 mm |
| NET WEIGHT | 63 kg |
| VOLUME | 0.5 m3 |
| ELECTRIC POWER | 18 kW |
| PHASE | 3N |
| FREQUENCY | 50/60 Hz |
| VOLTAGE | 400 V |

| | |
|---|---|
| WELL CAPACITY | 22 LT. |
| WELL DIMENSIONS | 240x420x180 mm |

SILKO ALI Group Srl

Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it

| SERIES | PRODUCT FAMILY | VERSION | MODEL |
|---|---|---|---|
| **900** | **FRYER** | **ELECTRONIC** | **NEFE92122E** |

## FEATURES:


Electronic Fryer, single well, Monoblock unit on base with hinged door. Cook top made of stainless steel AISI 304, thickness 20/10, pre-fitted for head-to head connection. Pressed well made of stainless steel AISI 304, with radiused inner profile. Well capacity in litres 22. Well with wide expansion area in the front part for oil and foam and extended cooling area in the front part for collection of food particles. Heating by means of shielded electrical resistance in stainless steel AISI 304 positioned inside the well. The resistances rotates over 90° to make cleaning procedures easier. Control and operational settings via backlit computer with touch technology, black musk. Precise temperature control at ° C, three timers integrated with buzzer and auto shut off to decrease power consumption, standby function with adjustable set point, audible and visual signals for set timings and temperatures, temperature also displayed when appliance is turned off, auto diagnose system to check that appliance is operating correctly and low voltage digital inputs to optimize power consumption. Electronic temperature control with settings between 100°C and 180°C. Manually resettable safety thermostat. Extractable filter, basket and lid and collector for drain cock included. Height-adjustable feet in stainless steel.

## OPTIONAL ACCESSORIES:

| | |
|---|---|
| • Basket 1/1 for 22 and 23 lt. well. | ECF22 |

| SERIES | PRODUCT FAMILY | VERSION | MODEL |
|---|---|---|---|
| **900** | **FRYER** | **ELECTRONIC** | **NEFE92122E** |

## INSTALLATION SCHEME




| | | | |
|---|---|---|---|
| E1 | SOCKET | 400 V | 3N |
| AF | COLD WATER | | |
| AC | HOT WATER | | |
| G | GAS | | |
| S | DRAINING | | |

NOTES FOR THE INSTALLER:
All water and gas connections must be fitted with a shut-off valve or ball valve.
Main gas connections must be provided of closing gate device.
Gas connections must not use welded tubes.
Gas connections must be jacketed according to current rules in the country.
Electric connections must be provided of safety switch and a minimum exit wire of 1,5 meter lenght ( except where otherwise required in the drawing).
All sockets must be built according to safety-rules in force. Suited for humid room and settled with necessary plug.
All electric connections must be provided of main switch.
The specification shown in this document are to be considered not bounding.
The company reserves the right to make technical changes at any moment.

SILKO ALI Group Srl
Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it