Data sheet

NEFGP9123A

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**FRYER**	**GAS**	**NEFGP9123A**



DESCRIPTION

GAS FRYER EVO 1 WELL 23 LT.HIGH PRODUCTIVITY, DIGITAL CONTROL, BASKET LIFTING SYSTEM

TECHNICAL DATA:

STRUCTURE	FLOOR
WIDTH	400 mm
DEPHT	900 mm
HEIGHT	900 mm
NET WEIGHT	62 kg
VOLUME	0.6 m3
GAS POWER	25 kW
ELECTRIC POWER	0.1 kW
FREQUENCY	50/60 Hz
VOLTAGE	230 V

WELL CAPACITY	23 LT.
WELL DIMENSIONS	340x420x200 mm
PRODUCTIVITY PER HOUR	26 kg/h

SILKO ALI Group Srl

Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**FRYER**	**GAS**	**NEFGP9123A**

FEATURES:


Single-well gas fryer with electronic control and high productivity, AISI 304 stainless steel. 20/10 thick stainless steel top with 300 mm splashback with integrated flue. Deep drawn cooking well in AISI 304 stainless steel, with curved internal corners. 23-litre well capacity. Wells with wide front expansion zone for oil and foam and extended cold zone for collection of food particles. Heating by means of 2 external stainless steel burners with optimised flame distribution. Thanks to 30 programs, the operator can easily select the type, quantity and holding temperature of product to be fried. The electronic control automatically adapts the cooking cycle based on the selection made. Control panel with 7" high-resolution touchscreen display with electronic control board for management of the cooking temperature from 0 to 185°C with a precision of ± 1°C. Management of HACCP alarms, the tank cleaning cycle, the preheating function and holding at 100°C, and system diagnostics. Safety thermostat with manual reset. System for automatic, programmable lifting of the two half baskets for frying. Comprised of 2 linear actuators that enable baskets to be lifted by 120 mm. and an acoustic signal to indicate the end of frying time. Equipped with: 1 mesh filter in chrome-plated steel for resting fryer baskets on; 2 half-baskets for frying in chrome-plated steel with front handle in heatproof material; 1 well lid; 1 extension for front drainage of well. Height adjustable feet in stainless steel.


OPTIONAL ACCESSORIES:

• COLLECTOR FOR FRYING RESIDUE	NXFIV23G
• DEFLECTOR FOR BATTERED FOOD	NX9DF23

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**FRYER**	**GAS**	**NEFGP9123A**

INSTALLATION SCHEME





E1	SOCKET	230 V	
AF	COLD WATER		
AC	HOT WATER		
G	GAS	Ø 1/2"	100 mm
S	DRAINING		

NOTES FOR THE INSTALLER:
All water and gas connections must be fitted with a shut-off valve or ball valve.
Main gas connections must be provided of closing gate device.
Gas connections must not use welded tubes.
Gas connections must be jacketed according to current rules in the country.
Electric connections must be provided of safety switch and a minimum exit wire of 1,5 meter lenght (except where otherwise required in the drawing).
All sockets must be built according to safety-rules in force. Suited for humid room and settled with necessary plug.
All electric connections must be provided of main switch.
The specification shown in this document are to be considered not bounding.
The company reserves the right to make technical changes at any moment.

SILKO ALI Group Srl
Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it