Data sheet

NEPE9D10

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**PANS**	**ELECTRIC**	**NEPE9D10**

DESCRIPTION

ELECTRIC PAN DIRECT HEATING 100 LITRES



TECHNICAL DATA:

STRUCTURE	100 LT.
WIDTH	800 mm
DEPHT	900 mm
HEIGHT	900 mm
NET WEIGHT	116 kg
VOLUME	1.1 m3
ELECTRIC POWER	12 kW
PHASE	3N
FREQUENCY	50/60 Hz
VOLTAGE	400 V

WELL CAPACITY	100 LT.
WELL DIMENSIONS	Ø 595x370 mm

SILKO ALI Group Srl

Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**PANS**	**ELECTRIC**	**NEPE9D10**

FEATURES:


Electric Boiling Pan, Monoblock unit with direct heating made of stainless steel AISI 304. Stainless steel top (AISI 304), thickness 20/10, pre-fitted for head-to-head connection. Pan bottom made of stainless steel AISI 316L, polished, sides made of stainless steel AISI 304. 100 lt. - well capacity. Hot or cold water is loaded through electric valve activated by a switch, fixed water tap positioned on the top. 2 safety drain tap with thermostable grip. Lid opening 90°, balanced by front and side handle. Direct heating via steel resistances (AISI 309) position outside the kettle. Thick insulating panels provide thermal insulation for the kettle. Temperature controlled via power regulator. Signal light checks whether the appliance is operating correctly. Kettle diameter 60 cm. Model with safety thermostat and rest button accessible to the user. Height-adjustable feet in stainless steel.


OPTIONAL ACCESSORIES:

• Pasta basket 2 sections 100lt.	0102329

SERIES	PRODUCT FAMILY	VERSION	MODEL
900	**PANS**	**ELECTRIC**	**NEPE9D10**

INSTALLATION SCHEME





E1	SOCKET	400 V	3N
AF	COLD WATER	Ø 3/4"	100 mm
AC	HOT WATER	Ø 3/4"	100 mm
G	GAS		
S	DRAINING		

NOTES FOR THE INSTALLER:
All water and gas connections must be fitted with a shut-off valve or ball valve.
Main gas connections must be provided of closing gate device.
Gas connections must not use welded tubes.
Gas connections must be jacketed according to current rules in the country.
Electric connections must be provided of safety switch and a minimum exit wire of 1,5 meter lenght (except where otherwise required in the drawing).
All sockets must be built according to safety-rules in force. Suited for humid room and settled with necessary plug.
All electric connections must be provided of main switch.
The specification shown in this document are to be considered not bounding.
The company reserves the right to make technical changes at any moment.

SILKO ALI Group Srl
Uff. Commerciali:
Via F. Marinotti 45
31029 Vittorio Veneto (TV) ITALY
Tel. (+39) 0438 911930
C.F. e P.I. 13239980967

Sede Second. E Uff. Amm.vi:
Via Schiaparelli, 15 – Z.I. S. Giacomo di Veglia
31029 Vittorio Veneto (TV) - ITALY
Tel. (+39) 0438 9110

Capitale Sociale € 20.000.000 I.V.
Società a Socio Unico
Sede Legale: Via Gobetti,2/A – 20063 Cernusco sul Naviglio (MI)
REA MI2711267- Registro Imprese Milano
www.silko.it - E-mail: info@silko.it